



CLEAN AIR AMERICA



WELDSTATION™ DUAL

Premier Fume Extraction Solutions for Trade Schools and Welding Labs

STANDARD FEATURES

Self-Contained for Enhanced Lab Safety

Plug-and-Play Functionality for Easy Installation

Dual 5' x 5' Table Design with Adjustable Shelf

Side-by-Side or Back-to-Back Configuration

VFD and Economizer Standard for Automatic Start, Increased Energy Savings, Noise Reduction, and Speed Control of the Motor

Enhanced Filter Life with Higher Active Filter Area and Improved Dust Release

Built-In Two-Stage Spark Arrestors and Standard with Fire Retardant Filters

Optional Weld Curtain for Improved Source Capture

SPECIFICATIONS

Air Flow: 4,000 CFM (2,000 CFM per Booth)

Filter Cartridges: Qty (4) Merv 11 Filters with 226sf of Fire Retardant Media (904sf total) – Available in Merv 15 Nano

Spark Arrestors: Qty (2) 24" x 24" x 2" Metal Spark Baffle plates and (2) 24" x 24" x 2" Metal Mesh Filters

Motor / Blower: 5HP, Direct Drive, Backward Inclined Blower

Power: Three Phase – 208, 240, or 460 Volt, 6A – 19A

Pulse Valves: Qty (2) 1" Pulsing Valves – auto or manual

Compressed Air: 1" NPT Compressed Air connection – 70-90 PSI required

Silencing: Internal Noise Abatement in motor/blower compartment for noise dampening (65 - 74dB at 5')

Dimensions: 116" L x 41" D x 124" H

Weight: 2,100 lbs – 12-Gauge Solid Weld Construction



Clean Air America -- 7 Superior Drive SE, Rome, GA 30161 – www.Clean-Air.com

Sales@Clean-Air.Com – 866.665.1829